

Allied Telesis™

GO! Phone

Quick install guide
V 1.0



HandyTone 286

WARNING: Please DO NOT power cycle the HandyTone during system boot up or firmware upgrade. You may corrupt firmware images and cause the unit to malfunction.

WARNING: Use only the power adapter included in the HandyTone package. Using an alternative non-qualified power adapter may possibly damage the unit.

Overview

Grandstream HandyTone Analog Telephone Adapters/IAD series offers a comprehensive line of affordable VoIP access devices based on Grandstream's innovative and proprietary technology platform. The HandyTone series offers the entry-level IP Telephony user superb audio quality, rich functionalities, interoperability with the leading 3rd party VoIP providers, and compatibility with most service providers. The HandyTone series is compact, works with any PSTN or cordless phone and fax machines and offers the simplicity of plug and dial, making it ideal for the basic IP telephony user.

**Equipment Packaging
Unpack and check all accessories**

1. One HandyTone Analog Telephone Adapter
2. One Universal Power Adaptor
3. One Ethernet Cable
4. Quick Installation Guide



THREE EASY STEPS TO INSTALL THE HT-286

1. Connect a standard touch-tone analog telephone (or fax machine) to FXS port.
2. Insert the Ethernet cable into the LAN port of HT-286 and connect the other end of the Ethernet cable to an uplink port (a router or a modem, etc.)
3. Insert the power adapter into the HT-286 and connect it to a wall outlet.
4. For a complete guide on how to use and configure all the features and options on your new Go! Phone please go here http://www.grandstream.com/user_manuals/HandyTone.pdf

